



CFR 8

ENGINE

Type	2-stroke
Displacement	794 cc
Cooling	Liquid
Cylinders	Twin
Bore x Stroke	85 x 70 mm
Lubrication	Oil injection
Ignition	3D
Carburetion	46 mm throttle body batteryless EFI
Exhaust	APV with tuned pipe, pipe sensor and canister
Fuel capacity	12.2 gal.

POWERTRAIN

Drive clutch	Arctic (rpm sensing)
Driven clutch	Arctic (roller cam) ACT drive system
Brakes	Hydraulic disc

SUSPENSION

Front suspension	AWS™ VI double-wishbone A-arms with lightweight aluminum FOX Zero Pro (IFP) shocks, adjustable preload springs with sway bar
Front travel	9.2 in.
Rear suspension	FasTrack Long-Travel System slide-rail, adjustable torsion springs, lightweight aluminum FOX Zero Pro (IFP) shocks with coupling blocks
Rear travel	13.5 in.

DIMENSIONS

Overall length	121 in.
Overall width	48 in.
Ski stance	42-44 in. (adjustable)
Track width	14 in.
Track length	128 in.
Lug	1.0 in.

COLOR

White

STANDARD FEATURES

Dual halogen (4-bulb) headlight, UHMW plastic saddleless ski material, Digital/analog tachometer, Digital/analog speedometer, Dual stage trip odometer, Mechanical gas gauge, Low oil light, Coolant overheat light, Altimeter, Reverse, High/low hand warmer, High/low thumb warmer, Spark plug holder, Belt holder, Deluxe gauge, Adjustable handlebars

OPTIONAL FEATURES

Tether switch, Hitch, 2-up seat, Mirrors, High windshield, Ice scratchers, Tank pads, Tunnel flares, Rack, Goggle holder, Storage bags, Tunnel deflectors, Hand guards

SUGGESTED RETAIL

\$10,699 - US

\$12,699 - CA



**INDUSTRY-LEADING
HORSEPOWER**



©2010 Arctic Cat Inc. All rights reserved. ™ and the Arctic Cat logo are trademarks of Arctic Cat Inc. Because of our ongoing commitment to product quality and innovation, Arctic Cat reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. See your dealer for details.